

Regional to licence-scale structural controls derived from structural mapping, geophysical analysis and 3D modelling of New Luika Gold Mine, Lupa Terrane, SW Tanzania

Dr C. Koegelenberg ⁽¹⁾

J.N. Gloyn-Jones ⁽¹⁾

Dr I. J. Basson ⁽¹⁾

P.W. Mbuya ⁽²⁾

A.M. Kulwa ⁽²⁾

S. Ramadhani ⁽²⁾

D. Daud ⁽²⁾

The Lupa Goldfields and encompassing Paleoproterozoic Lupa Terrane in southwestern Tanzania is known for its high prospectivity and is host to numerous artisanal gold mines and several relatively small- to medium-scale gold deposits that range broadly between 150 – 4000 kt at 1.5 – 5 g/t Au. Shanta Gold's New Luika Mine is currently the largest open and underground mine within the Lupa Goldfields and comprises at least 10 different deposits over an area of 18 km² with a combined resource of 1,105 koz at 2.56 g/t Au (2021). However, despite the conspicuous prospectivity of the region, comparative recent discoveries or extensions to known high-grade (> 4g/t) deposits has been elusive. The Lupa Terrane predominantly comprises a suite of Archaean granitoids (*ca.* 2.74 Ga) intruded by Palaeoproterozoic granites and gabbro-diorites (*ca.* 1.96 Ga), that reflect re-working of the southern margin of the Tanzania Craton during protracted deformation of the Ubendian Orogeny (2.1 – 1.88 Ga). Relatively late-tectonic auriferous quartz veins account for economic mineralization (*ca.* 1.88) Ga within narrow, mostly ductile, mylonitic shear zones developed under greenschist metamorphic conditions. From a regional- to deposit-scale mylonite zones are generally continuous and interconnected, which emphasizes an extensive, structurally controlled fluid conduit system. However, along these mylonite zones and away from known deposits, surface exploration records increasingly variable and often discontinuous along-strike auriferous mineralization, which suggests that new deposits or deposit extensions are likely not exposed on surface but hidden at greater depths.

To advance the understanding on the structural controls on mineralization this contribution presents a regional- to deposit-scale structural analysis that integrates aeromagnetic, field mapping, drillhole and soil geochemistry data over New Luika Mine and surrounding areas. Deposit-scale, fault-fill, auriferous vein-systems and associated mylonite fabrics are structurally and kinematically described and modelled in 3D, with the aim of establishing the structural controls on fluid flow and associated auriferous mineralization.

Results depict a 1st order or regional network of wide, incipient to intensely strained, oblique, left-lateral (transpressional-) shear zones (or "shear zone corridors"), which act as mineralized fluid conduits across several tens of kilometres. These shear zone corridors host well-developed, deposit-scale 2nd-3rd order mylonite zones

that are mineralized, to between *ca.* 1-3 g/t Au. Increased structural dilation and silicification along 2nd-3rd order mylonite zones within ¹⁾ 1st order release bends and/or ²⁾ that are unfavourably orientated with respect to the regional stress configuration exhibit increased auriferous grades (*ca.* 2-5 g/t Au). More locally, a combination of favourable kinematics, variable rock rheology and/or the reactivation of pre-existing contacts or structures cause steep- to shallow-plunging mesoscale release bends on 2nd-3rd order mylonites further accounting for highly mineralized (>6g/t Au) ore-shoot formation. Exploration following this rationale has significantly added to the resource at New Luika Gold Mine, while also providing a framework for regional exploration in the Lupa Goldfields, thereby re- emphasising the value of careful structural analysis in such structurally convoluted terranes.

Figure: Structural architecture and kinematics of the main shear zone corridor encompassing New Luika, Luika South and Bauhinia Creek Deposits.

